









S<u>onalika</u>



FEATURES60SAFETY SWITCHStandardClutch Safety SwitchStandardPTO Safety SwitchStandardNeutral Safety SwitchStandardCAPACITY (LTRS)(+/-5%)Fuel tank (Lit)Fuel tank (Lit)62TYREInterstep StatementFront9.5-24Rear16.9X28DIMENSION & WEIGHT(+/-5%)Yeight(kg)Weight(kg)2500Wheel Base (mm)2350Total Length (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1295-1650Fuel Indicator gaugeStandardFront Tow HookStandardFront Tow HookStandardFront Tailer HitchSwinging DrawbarROPSStandardTyresRear 9.5X20 / 16.9X28		
Clutch Safety SwitchStandardPTO Safety SwitchStandardNeutral Safety SwitchStandardCAPACITY (LTRS)(+/-5%)-Fuel tank (Lit)62TYRE-Front9.5-24Rear16.9X28DIMENSION & WEIGHT(+/-5%)2500Wheel Base (mm)2350Total Length (mm)3980Total Length (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS-Fuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront Tow HookStandard, inbuilt in front weightFront Track (mm)Standard, inbuilt in front weightFront Track Ith StandardSwinging DrawbarROPSStandardStandardStandard	FEATURES	60
PTO Safety SwitchStandardPTO Safety SwitchStandardNeutral Safety SwitchStandardCAPACITY (LTRS)(+/-5%)62Fuel tank (Lit)62TYRE16.9X28Pinter Sion & WEIGHT(+/-5%)2500Weight(kg)2500Wheel Base (mm)3980Total Length (mm)3980Total Length (mm)3980Total Width (mm)1790-1950Height (mm) Up to ROPS2650Rear Track (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERSFuel Indicator gaugeFront Tow HookStandardFront Tow HookStandard, inbuilt in front weightFront Trailer HitchSwinging DrawbarROPSStandardROPSStandardOTIONAL FEATURESStandard	SAFETY SWITCH	
Neutral Safety SwitchStandardNeutral Safety SwitchStandardCAPACITY (LTRS)(+/-5%)-Fuel tank (Lit)62TYRE-Front9.5-24Rear16.9X28DIMENSION & WEIGHT(+/-5%)-Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Length (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS-Fuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront Track mith std. BallastBase Weight 72Kg+Front 6X31 KgTrailer HitchSwinging DrawbarROPSStandard	Clutch Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)Fuel tank (Lit)62TYRE9.5-24Front9.5-24Rear16.9X28DIMENSION & WEIGHT(+/-5%)2500Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Width (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS5tandardFuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgROPSStandardOTHIONAL FEATURESVandard	PTO Safety Switch	Standard
Fuel tank (Lit)62TYREFront9.5-24Rear16.9X28DIMENSION & WEIGHT(+/-5%)Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Length (mm)2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS5Fuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront Tow HookStandardROPSStandardROPSStandardOTHONAL FEATURES	Neutral Safety Switch	Standard
TYREFront9.5-24Rear16.9X28DIMENSION & WEIGHT(+/-5%)2500Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Length (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS1420-1880Fuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront Tow HookStandard, inbuilt in front weightROPSStandardOTHENSStandard	CAPACITY (LTRS)(+/-5%)	
Front9.5-24Rear16.9X28DIMENSION & WEIGHT(+/-5%)Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Width (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERSFuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgROPSStandardOTHIONAL FEATURES	Fuel tank (Lit)	62
Rear16.9X28DIMENSION & WEIGHT(+/-5%)Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Length (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS5Fuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgROPSStandardOTHIONAL FEATURESStandard	TYRE	
DIMENSION & WEIGHT(+/-5%)Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Length (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERSFuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgROPSStandardOTTIONAL FEATURES	Front	9.5-24
Weight(kg)2500Wheel Base (mm)2350Total Length (mm)3980Total Width (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERSFontFuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgROPSStandardOTTIONAL FEATURESStandard	Rear	16.9X28
Wheel Base (mm)2350Total Length (mm)3980Total Width (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERSFont Track (mm)Fuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgROPSStandardOTTIONAL FEATURESStandard	DIMENSION & WEIGHT(+/-5%)	
Total Length (mm)3980Total Width (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS	Weight(kg)	2500
Total Width (mm)1790-1950Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERSFuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgTrailer HitchSwinging DrawbarROPSStandardOTTIONAL FEATURESStandard	Wheel Base (mm)	2350
Height (mm) Up to ROPS2650Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS5Fuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgTrailer HitchSwinging DrawbarROPSStandardOTTIONAL FEATURESStandard	Total Length (mm)	3980
Min Ground Clearance (mm)360Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERS	Total Width (mm)	1790-1950
Front Track (mm)1295-1650Rear Track (mm)1420-1880OTHERSFuel Indicator gaugeStandardFront Tow HookStandard, inbuilt in front weightFront & rear weights with std. BallastBase Weight 72Kg+Front 6X31 KgTrailer HitchSwinging DrawbarROPSStandardOPTIONAL FEATURES	Height (mm) Up to ROPS	2650
Rear Track (mm) 1420-1880 OTHERS Fuel Indicator gauge Standard Front Tow Hook Standard, inbuilt in front weight Front & rear weights with std. Ballast Base Weight 72Kg+Front 6X31 Kg Trailer Hitch Swinging Drawbar ROPS Standard OPTIONAL FEATURES	Min Ground Clearance (mm)	360
OTHERS Standard Fuel Indicator gauge Standard Front Tow Hook Standard, inbuilt in front weight Front & rear weights with std. Ballast Base Weight 72Kg+Front 6X31 Kg Trailer Hitch Swinging Drawbar ROPS Standard OPTIONAL FEATURES Standard	Front Track (mm)	1295-1650
Fuel Indicator gauge Standard Front Tow Hook Standard, inbuilt in front weight Front & rear weights with std. Ballast Base Weight 72Kg+Front 6X31 Kg Trailer Hitch Swinging Drawbar ROPS Standard OPTIONAL FEATURES Standard	Rear Track (mm)	1420-1880
Front Tow Hook Standard, inbuilt in front weight Front & rear weights with std. Ballast Base Weight 72Kg+Front 6X31 Kg Trailer Hitch Swinging Drawbar ROPS Standard OPTIONAL FEATURES Standard	OTHERS	
Front & rear weights with std. Ballast Base Weight 72Kg+Front 6X31 Kg Trailer Hitch Swinging Drawbar ROPS Standard OPTIONAL FEATURES	Fuel Indicator gauge	Standard
Trailer Hitch Swinging Drawbar ROPS Standard OPTIONAL FEATURES	Front Tow Hook	Standard, inbuilt in front weight
ROPS Standard OPTIONAL FEATURES	Front & rear weights with std. Ballast	Base Weight 72Kg+Front 6X31 Kg
OPTIONAL FEATURES	Trailer Hitch	Swinging Drawbar
	ROPS	Standard
Tyres Rear 9.5X20 / 16.9X28	OPTIONAL FEATURES	
	Tyres	Rear 9.5X20 / 16.9X28

*Since product improvement is a continuous process, speci cation and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP

FEATURES	60
Model Description	Sonalika-60
ENGINE	
Engine Type	3100 FLT
HP Category	60
No. of Cylinders	3
Aspiration	Turbo
Cubic Capacity (cc)	2780
Rated RPM	2100
Air cleaner	Dry Type
Cold Start	Standard
Max Torque (Nm)	230Nm@1300erpm
Exhaust	Underhood / Upward
TRANSMISSION	
Drive	4WD
Clutch	Dual Clutch
Gearbox	8F+2R
Front Axle	4WD
Transmission	Swift Shift
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	33.67
Minimum Speed (Km/Hr)	2.52
BRAKES	
Brakes	Oil Immersed Brake
Type of actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK	
Di erential lock	Standard
РТО	
PTO (rpm)	540
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 88Ah
Alternator	12V, 36Amp
Seven pin trailer socket	Standard
HYDRAULICS	
3 point linkage	CAT-II
Stay Bars	Swinging Drawbar
Hydraulic lifting capacity	2000 kg

2DA

Standard

Auxiliary hydraulic circuit

Lift rods

HEAVY DUTY

KK FOR YOUR FIELD XX

GE •

RACTOR R

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221 Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com