

# SONALIKA

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

## N75



ORCHARD/VINEYARD  
FARMING SPECIALIST

TURBO CHARGED  
ENGINE

HEAVY LIFT  
CAPACITY

CARRARO  
DRIVE LINE

HVAC/HEATER  
CABIN (OPTIONAL)



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH  
YANMAR**

**THE TOUGHEST  
PERFORMER  
« FOR YOUR FIELD »**

**N75**

**SONALIKA**



FEATURES	N 75
Model Description	SONALIKA N75
<b>ENGINE</b>	
Engine Type	4100 FLT Inline, Turbo Charged
HP Category	75
No. of Cylinders	4
Aspiration	Turbocharged
Cubic Capacity (cc)	3707
Rated RPM	2200
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	278 @ 1200
Exhaust	Underhood Downdraft Towards the Floor
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Front Axle	4WD
Transmission	Synchromesh
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	31.7 @ 2200
Minimum Speed (Km/Hr)	0.5 @ 2200
<b>BRAKES</b>	
Brakes	Oil Immeresed Brakes
Type of Actuation	Mechanical
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential Lock	Standard, Foot Operated
<b>PTO</b>	
PTO (RPM)	540/540E
PTO (Actuation)	Mechanical
<b>STEERING</b>	
Steering	Power
<b>ELECTRICAL</b>	
Battery	12V, 85Ah
Alternator	12V, 90Amp
Seven Pin Trailer Socket	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	CAT-II
Stay Bars	Standard
Hydraulic Lifting Capacity	2500 Kg
Auxiliary Hydraulic Circuit	2DA/2SA
Lift Rods	Standard

FEATURES	N 75
<b>SAFETY SWITCH</b>	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
<b>CAPACITY (LTRS) (+/-5%)</b>	
Fuel Tank (Lit)	71
<b>TURNING RADIUS</b>	
Without Brakes (m)	3.6
<b>TYRE</b>	
Front	8-18
Rear	14.9-24
<b>DIMENSIONS &amp; WEIGHT(+/-5%)</b>	
Overall Length (mm)	4240
Overall Width (mm)	1475
Overall Height upto ROPS (mm)	2700
Wheel Base (mm)	2306
Min. Ground Clearance (mm)	265
Front Wheel Track Agri (mm)	1150
Rear Wheel Track Agri (mm)	1082
Flange to Flange Distance Front/Rear	1155mm/892mm
<b>OTHERS</b>	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard, Inbuilt in Front Weight
Front & Rear Weights with Std. Ballast	Front-72 Kg Base wt 31x6Kg Front Removal Weight (Rear: 2X30Kg)
Trailer Hitch	Swinging Drawbar
ROPS	Mid Mounted Foldable
<b>OPTIONAL FEATURES</b>	
Tyres	Front- 210/95/R18, Rear-360/70/R28 Front - 280/70R18, Rear- 360/70R28 Front - 260/70R16, Rear- 360/70R24
Cabin	HVAC / Heater
Front Mudguard	Standard
Trailer Brake	HTB
Front Tyre 2WD	6.5x16

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, please correlate with latest updates. Accessories shown may not be part of standard product.

**DEALER STAMP**



SONALIKA N75 AF

**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.sonalika.com/www.solisworld.com