

# SONALIKA

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

**75**



AGILE 4 CYLINDER  
ENGINE

8F+2R CONSTANT MESH  
TRANSMISSION

HEAVY LIFT  
CAPACITY

TWIN PROJECTOR  
HEADLAMPS

INTEGRATED SAFETY  
HVAC CABIN (OPTIONAL)



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH  
YANMAR**

**THE TOUGHEST  
PERFORMER  
«FOR YOUR FIELD»**

**S75**

**SONALIKA**



FEATURES	75 RX
Model Description	SONALIKA 75
<b>ENGINE</b>	
Engine Type	4100FLT
HP Category	75
No. of Cylinders	4
Aspiration	Turbo Charged
Cubic Capacity (cc)	3707
Rated RPM (+/-25mm)	2200
Air Cleaner	Dry Type with Clogging Sensor
Cold Start	Standard
Max Torque (nm) (+/-5%)	278@1300erpm
Exhaust	Elliptical Upward
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Dual Clutch
Gearbox	8F+2R
Transmission	Swift Shift
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	36.46 @ 2200
Minimum Speed (Km/Hr)	1.95 @ 2200
<b>BRAKES</b>	
Brakes	Oil Immersed Brakes
Type of Actuation	Mechanical
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential Lock	Standard, Foot Operated
<b>PTO</b>	
PTO (RPM)	540
PTO (Actuation)	Mechanical
<b>STEERING</b>	
Steering	Power
<b>ELECTRICAL</b>	
Battery	12V, 110/88 Ah
Alternator	12V, 36Amps
Seven Pin Trailer Socket	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	CAT-II
Stay Bars	Adjustable
Hydraulic Lifting Capacity	2000Kg
Auxiliary Hydraulic Circuit	1DA+1SA
Lift Rods	Standard

FEATURES	75 RX
<b>SAFETY SWITCH</b>	
Neutral Safety Switch	Standard
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
<b>CAPACITY (LTRS) (+/-5%)</b>	
Fuel Tank (Ltr)	65
<b>TYRE</b>	
Front	11.2 - 24
Rear	16.9-30
<b>DIMENSIONS &amp; WEIGHT(+/-5%)</b>	
Unballast Weight	2742
Wheel Base (mm)	2307
Total Length (mm)	3997
Total Width (mm)	1942
Height (mm) up to ROPS	2620
Min. Ground Clearance (mm)	293
Front Track (mm) (Standard)	1672
Rear Track (mm) (Standard)	1515
<b>OTHERS</b>	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard, Inbuilt in Front Weight
Front & Rear Weights with Std. Ballast	Front- 30KgX2, 25X4 , Rear- 1X34 Kg
Trailer Hitch	Swinging Drawbar
ROPS	Standard
<b>OPTIONAL FEATURES</b>	
Canopy	Optional
2WD Variant	Standard
Tyre 2WD	Front: 7.5X16

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, please correlate with latest updates. Accessories shown may not be part of standard product.

**DEALER STAMP**



SONALIKA S75 8+2 AF

**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.sonalika.com/www.solisworld.com