

SONALIKA

PERFECTED FOR HAULAGE AND AGRICULTURAL NEEDS

VALUE FOR MONEY
EXTRA DURABILITY
DIVERSE APPLICATIONS







SONALIKA



Engine

• Fuel Efficient, Single Cylinder 863cc Engine



Hydraulics

 Powerful High Lift Capacity of 700 Kg



Transmission

• Tough Transmission 6 Forward + 2 Reverse Speeds



Compact Design

• Ideal for Sugarcane, Cotton etc.

www.international.sonalika.com

SONALIKA

SPECIFICATIONS

FEATURES	FP-18
ENGINE	
HP Category	18
No. of Cylinder	1
Aspiration	Natural
Cubic Capacity	863.5 cc
Rated RPM	2300 ± 75
Air Cleaner	Dry type
Max Torque (Nm)	54@1200±200 RPM
Exhaust	Updraft Silencer
TRANSMISSION	
Drive	2WD
Gearbox	Sliding Mesh
Transmission	6F + 2R
SPEED (FORWARD)	
Minimum Speed (Km/hr)	2.01
Maximum Speed (Km/hr)	25.19
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent Parking Brakes
РТО	
PTO (rpm)	540 & 540E
PTO (Actuation)	Mechanical
STEERING	
Steering	Mechanical
ELECTRICALS	
Battery	12V, 65 Ah
Alternator	12V, 36 H

^{*}Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tires.

FEATURES	FP-18
HYDRAULICS	
3 Point Linkage	CAT 1
Stay Bars	Anchor Chain
Auxiliary Hydraulic Circuit	1TA
Lift Capacity	700 kg
Lift Rods	Yes
CAPACITY (LITRES ± 5%)	
Fuel Tank	28 L
TYRE	
Front	5.25 X 14
Rear	8 X 18
OVERALL DIMENSIONS	
Weight (Kg)	1160
Wheel Base (mm)	1485
Total Length (mm)	2745
Total Width (mm)	1165
Height (mm) Up to Muffler	1780
Min. Ground Clearance	220
Front Track (mm)	970
Rear Track (mm)	935
OTHERS	
Front Toe Hook	Yes, Available



DEALER STAMP

INTERNATIONAL TRACTORS LIMITED